

PRODUCT DATA SHEET

Reviewed 01/02/2016



YOU CAN'T BUY A BETTER PAINT FOR LESS!™



Premium Supa Satin Acrylic

- SECTION A: DESCRIPTION**
A sheen acrylic paint for interior and exterior surfaces of the highest quality formulated to meet the specification of S.A.B.S.1586 Grade 1, with excellent durability. Available in popular standard colours and in thousands of others. Imparts a beautiful sheen finish that is fully washable and stain resistant. Contains "WAX SHIELD" additives for improved stain resistance and contains "FUNGAL SHIELD" advanced anti-fungal benefits with superior mould & alkali resistance.
- SECTION B: COMPOSITION**
Pure acrylic emulsion paint.
- SECTION C: PHYSICAL PROPERTIES**
- | | |
|---------------------|--|
| Colour: | White, Colour Card, Tint Bases |
| Appearance: | Sheen |
| Gloss: | 45 - 45% @ 85° |
| Viscosity: | 95 - 115 Ku @ 25°C (depending on colour) |
| S.G.: | 1.24 - 1.29 |
| Mass Solids: | 45 - 50% |
| Volume Solids: | 31 - 36% |
| Shelf Life: | 12 Months |
| Storage Conditions: | Normal |
| Pack Size: | 1ℓ, 5ℓ, 20ℓ |
- SECTION D: APPLICATION PROPERTIES**
- | | |
|--------------------------|---|
| Method: | Brush, airless spray, roller |
| Spreading Rate: | 10 - 12m ² /ℓ |
| Number of coats: | 2 |
| Drying Time @ 25°C: | Hard 4hrs (depending on moisture and humidity). Allow 14 days to cure before washing. |
| Overcoating Time @ 25°C: | 4hrs |
| Cleaning Solvent: | Water |
| Recommended systems: | As described above |
- SECTION E: PRECAUTION**
- | | |
|--------------|--------------|
| Flash point: | water-based |
| Toxicity: | See M.S.D.S. |
- SECTION F: SURFACE PREPARATION**
- All surfaces to be thoroughly clean, dry and free from grease, dirt or flaking paint.
 - All loosely adhering material and powder such as distemper or lime must be removed, and a coat of Excelsior SURFCON (Surface Conditioner) applied and allowed to dry (± 18 hours).
- GALVANISED IRON**
- Remove storage oil with GI CLEANER and prime with one coat of Excelsior AQUA METALPRIME anti-corrosive primer.
- MILD STEEL**
- Prime with Excelsior H2O PRIMER RED OXIDE PRIMER etching water-based primer. (NEW FORMULATION!!)
 - Alkyd based Excelsior GP RED OXIDE PRIMER or Excelsior ZP PRIMER (with anti-corrosive zinc-phosphate pigments).
- FRESH PLASTER**
- Once plaster is completely dry. Apply one coat of either:
- Excelsior AQUA-PLASTER PRIMER (water-based).
 - or Excelsior PLIOLITE PLASTER PRIMER (Goodyear France technology) (solvent-based).
 - or Excelsior ALKALI RESISTANT PLASTER PRIMER (solvent-based).

PRODUCT DATA SHEET

Reviewed 01/02/2016



YOU CAN'T BUY A BETTER PAINT FOR LESS!™

Premium Supa Satin Acrylic.../continued

PREVIOUSLY PAINTED EMULSION (PVA/ACRYLIC) SURFACES

- Loose material must be removed with sandpaper.
- Powdery surfaces sealed with Excelsior SURFCON (Surface Conditioner).
- Dirt or grime to be removed with sugar soap.

PREVIOUSLY PAINTED ENAMEL (Hi-gloss or Eggshell) SURFACES

- Sandpaper thoroughly
- Apply one coat of Excelsior
- Universal Undercoat and allow \pm 18hr to dry.

IMPORTANT!

- Stir well before use.
- Allow 7 days for paint to cure fully before washing.

SECTION F:

NOTE

No guarantees are implied by the recommendations contained herein; since the data sheet is issued for information only. Method of application, surface cleanliness, conditions of use etc. are beyond our control.